



N-type i-TOPCon Ultra

DUAL GLASS MONOCRYSTALLINE MODULE

TSM-NEG9RP.25Z 460-480W

480_W MAXIMUM POWER OUTPUT

24.0% MAXIMUM EFFICIENCY



Premium full black aesthetic

- Uniform, all-black, full-screen high density interconnection for a seamless design with no cell gaps



High power & efficiency

- Up to 480 W and 24% efficiency with low-voltage, high-current architecture for more power on limited roof space



Optimised performance


- Lower temperature coefficient and strong low-irradiance performance maximises power generation on rooftops



Long-term value for residential homes

- Low annual degradation backed by up to 30 year power warranty and 25 year product warranty

Performance Warranty



* Please refer to product warranty for details

Comprehensive Products and System Certificates

IEC61215/IEC61730/IEC61701/IEC62716

ISO 9001: Quality Management System

ISO 14001: Environmental Management System

ISO14064: Greenhouse Gases Emissions Verification

ISO45001: Occupational Health and Safety Management System



*For ground-mounted installation, please consult Trinasolar sales team.

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2026 Trina Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co.,Ltd.

Version number: TSM_EN_2026_B

Trinasolar

ELECTRICAL DATA (STC)

Peak Power Watts- $P_{MAX}(W_p)^*$	460	465	470	475	480
Power Selection (W)**	0 ~ +5				
Maximum Power Voltage- V_{MPP} (V)	30.90	31.20	31.50	31.80	32.00
Maximum Power Current- I_{MPP} (A)	14.89	14.91	14.93	14.96	15.00
Open Circuit Voltage- V_{oc} (V)	36.90	37.10	37.30	37.40	37.70
Short Circuit Current- I_{sc} (A)	15.93	15.96	15.99	16.02	16.05
Module Efficiency η_m (%)	23.0	23.3	23.5	23.8	24.0

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: $\pm 3\%$. **Power selection up to: +3%.

ELECTRICAL DATA (NOCT)

Peak Power Watts- $P_{MAX}(W_p)$	349	353	357	361	364
Maximum Power Voltage- V_{MPP} (V)	29.00	29.20	29.40	29.60	29.80
Maximum Power Current- I_{MPP} (A)	12.06	12.11	12.16	12.20	12.23
Open Circuit Voltage- V_{oc} (V)	35.00	35.20	35.40	35.60	35.80
Short Circuit Current- I_{sc} (A)	12.80	12.83	12.85	12.88	12.90

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature) 43°C ($\pm 2^\circ\text{C}$)

Temperature Coefficient of P_{MAX} -0.26% /°C

Temperature Coefficient of V_{oc} -0.24% /°C

Temperature Coefficient of I_{sc} 0.04% /°C

Due to different testing methods, the actual performances might differ from the declared specifications.

APPLICATION CONDITIONS


Operating Temperature -40~+70°C

Maximum System Voltage 1500V DC (IEC)


Max Series Fuse Rating 30A

CURVES OF PV MODULE

I-V CURVES OF PV MODULE (475W)




P-V CURVES OF PV MODULE (475W)



MECHANICAL DATA

Solar Cells	N-type i-TOPCon Monocrystalline
No. of cells	150 cells
Module Dimensions	1762×1134×30 mm (69.37×44.65×1.18 inches)
Weight	21.7 kg (47.84lb)
Front Glass	1.6mm (0.06inches), AR Coating Heat Strengthened Glass
Back Glass	1.6mm (0.06inches), Heat Strengthened Glass
Frame	30mm(1.18 inches) Anodized Aluminium Alloy, Black
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 6.0mm ² (0.009 inches ²) Landscape :1100/1100 mm(43.31/43.31 inches) Length can be customized
Connector	TS4 Plus / TS4 / MC4 EV02*
Packaging	Modules per box: 37 pieces Modules per 40' container: 962pieces

*The connector names listed are general names; specific types are subject to the certification documents.



www.trinasolar.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
© 2026 Trina Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.
The right of final interpretation belongs to Trina Solar Co.,Ltd.
Version number: TSM_EN_2026_B