

Parameters		DELTA Pro 3 EU Version
General	Color	Silver
	Capacity	4096Wh
	1 Unit Capacity Extend	12kWh
	Max Extend Range	12kWh
	Dimension(L*W*H)	Approx. 693mm*341mm*410mm
	Net.Weight(KG)	Approx. 51.5kg (113.54 lb)
AC Output	Max Continuous Output	4000W Max
	Surge Output	8000W, 400ms
	Output Voltage	230V
	X-Boost	6000W, Max
	X-Fusion	Yes, 230V/2900W AC input, 4000W.Max AC output
	X-Stream	Yes
	EPS/UPS	<10ms, UPS
	AC Power IN/OUT Port(Discharge Only)	230V~17.4A 50Hz
	AC Outlets Number	5
	AC Outlets	4x Type F, 230V/16A1x CEE 16A, 230V/16A
DC Output	USB-C	USB-C*2, 5/9/12/15/20V 5A 100W Max
	USB-A-Fast	USB-A*2, 5V 2.4A 9V 2A 12V 1.5A 18W Max
	Car Power Output	No
	12V DC Output	12.6V/30A 378W Total DC5521, 1X, 5A Max Anderson, 1X, 30A Max
	Remote Control Port	1X
Input	Utility Power Charging	C20 port,220-240V 12.5A 50/60Hz2900W MaxBypass
	Adjustable AC Charging Speed	Yes
	EV Charger Charging (AC Power IN/OUT Port)	AC Power IN/OUT Port4000W Max, 220-240V 20A 50
	Solar Input	2600W, Max 2 Ports, HPV:30-150V/15A, 1600W Max LPV:11-60V/20A, 1000W Max
	Car Input	12V 8A Max. 48V 20A Max.
	Generator Input	3200W, Max(with Smart generator 4000)
	0-80% Charge time	50min(1C Charging)
	Bond Charge Input (with 1*EB)	7000W, Max
Battery	Extra Battery Port	2X, Support DP EB, DP3 EB
	Battery Material	LFP
	Life Cycle	>4000cyc, 80%
	IP rate for Battery Pack	IP65
	CTC Craftsmanship	yes
	Smart Home Panle	no

